

# Drush 3.0 Beta 1 Cheatsheet

Options	Help
<code>-r &lt;path&gt;, --root=&lt;path&gt;</code>	Drupal root directory to use (default: current directory)
<code>-l &lt;uri&gt;, --uri=http://example.com</code>	URI of the drupal site to use (only needed in multisite environments)
<code>-v, --verbose</code>	Display extra information about the command.
<code>-d, --debug</code>	Display even more information, including internal messages.
<code>-q, --quiet</code>	Hide all output
<code>-y, --yes</code>	Assume 'yes' as answer to all prompts
<code>-n, --no</code>	Assume 'no' as answer to all prompts
<code>-s, --simulate</code>	Simulate all relevant actions (don't actually change the system)
<code>-i, --include</code>	A list of paths to search for drush commands
<code>-c, --config</code>	Specify a config file to use. See <code>example.drushrc.php</code>
<code>-u, --user</code>	Specify a user to login with. May be a name or a number.
<code>-b, --backend</code>	Hide all output and return structured data (internal use only).
<code>-p, --pipe</code>	Emit a compact representation of the command for scripting.
<code>--nocolor</code>	Suppress color highlighting on log messages.
<code>-h, --help</code>	This help system.
<code>--php</code>	The absolute path to your PHP interpreter, if not 'php' in the path.

Commands	Help
<code>cache-clear (cc)</code>	Clear a specific cache, or all drupal caches.
<code>cron</code>	Run all cron hooks.
<code>help</code>	Print this help message. Use <code>--filter</code> to limit command list to one command file (e.g. <code>--filter=pm</code> )
<code>hook</code>	List implementations of a given hook and explore source of specified one.
<code>php-eval</code>	Evaluate arbitrary php code after bootstrapping Drupal.
<code>php-script (scr)</code>	Run php script(s).
<code>pm-disable (dis)</code>	Disable one or more modules or themes.
<code>pm-download (dl)</code>	Download core Drupal and projects like CCK, Zen, etc.
<code>pm-enable (en)</code>	Enable one or more modules or themes.
<code>pm-info</code>	Show info for one or more projects.
<code>pm-list (sm)</code>	Show a list of available modules and themes
<code>pm-refresh (rf)</code>	Refresh update status information
<code>pm-releases</code>	Release information for a project
<code>pm-uninstall</code>	Uninstall one or more modules.
<code>pm-update (up)</code>	Update your project code and apply any database updates required (update.php)
<code>pm-updatecode (upc)</code>	Update your project code
<code>rsync</code>	Rsync the Drupal tree to/from another server using ssh. Relative paths start from the Drupal root folder if a site alias is used; otherwise they start from the current working directory.

Commands	Help
search-index	Index the remaining search items without wiping the index.
search-reindex	Force the search index to be rebuilt.
search-status	Show how many items remain to be indexed out of the total.
site-alias (sa)	Print site alias records for all known site aliases and local sites.
site-install (si)	Install Drupal along with modules/themes/configuration using the specified install profile.
site-upgrade (sup)	Run a major version upgrade for Drupal core and contrib modules.
sql-cli (sqlc)	Open a SQL command-line interface using Drupal's credentials.
sql-conf	Print database connection details using <code>print_r()</code> .
sql-connect	A string for connecting to the DB.
sql-dump	Exports the Drupal DB as SQL using mysqldump.
sql-query (sqlq)	Execute a query against the site database.
sql-sync	Copy source database to target database using rsync.
status (st)	Provides a birds-eye view of the current Drupal installation, if any.
test-clean	Delete leftover tables and files from prior test runs.
test-drush	Run drush-specific tests
test-mail	Run all tests and mail the results to your team.
updatedb (updb)	Execute the update.php process from the command line
variable-delete (vdel)	Delete a variable.
variable-get (vget)	Get a list of some or all site variables and values.
variable-set (vset)	Set a variable.
watchdog-delete (wd-del, wd-delete)	Delete watchdog messages.
watchdog-list (wd-list)	Show available message types and severity levels. A prompt will ask for a choice to show watchdog messages.
watchdog-show (wd-show, ws)	Show watchdog messages.
bam backup	Backup the site's database with Backup and Migrate.
bam backups	Get a list of previously created backup files.
bam destinations	Get a list of available destinations.
bam profiles	Get a list of available settings profiles.
bam restore	Restore the site's database with Backup and Migrate.
bam sources	Get a list of available sources.
generate content (genc)	Creates content.
generate-taxonomy (gent)	Creates taxonomy.
generate-users (genu)	Creates users.